



Building a better view.

PRODUCT SUMMARY & PERFORMANCE DATA		
6000C HS & 6500 Fixed - Aluminum Window		
AAMA Rating	H-C50	F-C70
Test Size	6' 0" X 5' 0"	6' 0" X 6' 0"
Frame Depth	3 1/4"	3 1/4"
Insulated Glass Thickness	7/8"	7/8"
Air Infiltration (25 mph) (cfm/sqft)	0.12	0.01
Water Test Pressure (psf)	7.5	12.0
Structural Load (psf)	75	105
Operating Force (lbf)	25	n/a
STC Range	28 - 39	28 - 37
OITC Range	23 - 31	22 - 31
Thermal Ratings (Typ)	Horizontal Slider	Fixed
U Value Range	.40 - .63	.28 - .54
SHGC Range	.61 - .29	.71 - .25
Other certified thermal packages are available. Please contact WinTech for the most current ratings		
Thermal Properties per NCTL-110-15425-01		
<p>The Wintech Series 6000 consists of 3 1/4" frame commercial aluminum windows with poured urethane thermal barriers. Model 6000 is a horizontal sliding window with a rating of HS-C50 and Model 6500 is a fixed window with a rating of F-C70. Both windows have the versatility of mulling and stacking. Twin horizontal sliding windows may be supplied pre-assembled with H-Mullions. These windows are available with integral frame flanges for replacement or new construction applications. The windows are supplemented with a complete line of panning, trim, mullions, and other accessories.</p>		
	15 Old Stonebreak Rd Malta NY 12020 518-899-9000 • 518-899-4104fx	