



Building a better view.

PRODUCT SUMMARY & PERFORMANCE DATA			
6500-7500-8500 Fixed - Aluminum Window			
AAMA Rating	F-HC70	F-CW50	F-AW50
Test Size	6' 0" X 6' 0"	5' 0" X 5' 0"	5' 0" X 8' 0"
Frame Depth	3 1/4"		
Insulated Glass Thickness	7/8"		
Air Infiltration (25 mph) (cfm/sqft)	0.01		
Water Test Pressure (psf)	12.0		
Structural Load (psf)	105	120	150
STC Range	28 - 37		
OITC Range	22 -31		
U Value Range	.28-.54		
SHGC Range	.71-.21		
Many certified thermal packages are available. Please contact WinTech for the most current ratings			
NCTL-110-15427-01			
<p>This Wintech series consists of 3 1/4" frame commercial aluminum windows with poured urethane thermal barriers. Model 6500-7500-8500 is a fixed window with ratings of F-HC70, CW50 & AW50. Windows have the versatility of mulling and stacking. Twin or triple fixed windows may be supplied pre-assembled with horizontal and/or vertical imposts. Windows are available with equal leg, 1 1/2" integral frame flange for replacement or 1" for new construction.</p>			
<div style="display: flex; justify-content: space-between; align-items: center;"> <div data-bbox="232 1728 386 1850" data-label="Image"> </div> <div data-bbox="557 1705 1060 1782" data-label="Text"> <p>15 Old Stonebreak Rd Malta NY 12020 518-899-9000 • 518-899-4104fx</p> </div> <div data-bbox="1266 1722 1401 1850" data-label="Image"> </div> </div> <p style="text-align: center;">www.windowtechsystems.net</p>			