

WINDOW TECH SYSTEMS
WinTech 
 Building a better view.

PRODUCT SUMMARY & PERFORMANCE DATA

7000C DH & 7500 Fixed - Aluminum Window

| | | | |
|--|----------------------|----------------------|----------------------|
| AAMA Rating | H-C50 | H-C60 | F-C70 |
| Test Size | 4' 6" X 7' 6" | 4' 0" X 6' 0" | 6' 0" X 6' 0" |
| Frame Depth | 3 1/4" | 3 1/4" | 3 1/4" |
| Insulated Glass Thickness | 7/8" | 7/8" | 7/8" |
| Air Infiltration (25 mph) (cfm/sqft) | 0.14 | 0.14 | 0.01 |
| Water Test Pressure (psf) | 8.25 | 9.0 | 12.0 |
| Structural Load (psf) | 75 | 90 | 105 |
| Operating Force (lower sash of 54x90) | Up: 24 lbf | Down: 18 lbf | n/a |
| STC Range | 29 - 38 | | 28 - 37 |
| OITC Range | 24 - 33 | | 22 - 31 |

| | | | |
|------------------------|------------------|------------------|------------------|
| Thermal Ratings | DH | | Fixed |
| | TYPICAL | AVAILABLE | TYPICAL |
| U Value Range | .62 - .43 | .41 - .37 | .54 - .34 |
| SHGC Range | .60 - .29 | .28 - .20 | .71 - .35 |

Other certified thermal packages are available. Please contact WinTech for the most current ratings

NCTL-110-15431-01

The Wintech Series 7000 consists of 3 1/4" frame commercial aluminum windows with poured urethane thermal barriers. Model 7000 is a double hung window with ratings of DH-C50:C60 and Model 7500 is a fixed window with a rating of F-C70. Both have the versatility of mulling and stacking. Twin or triple double hung windows may be supplied pre-assembled with common jamb mullions and continuous headers and sills. These windows are available with equal leg, 1 1/2" integral frame flange for replacement or 1" for new construction, and are supplemented with a complete line of panning, trim, mullions, and other accessories.



15 Old Stonebreak Rd Malta NY 12020
 518-899-9000 • 518-899-4104fx

