



Building a better view.

**PRODUCT SUMMARY & PERFORMANCE DATA**

**9000HC DH & 9500 Fixed - Aluminum Window**

AAMA Rating	H-HC45	H-HC60	F-HC70
Test Size	5' 0" X 8' 0"	4' 6" X 7' 0"	6' 0" X 6' 0"
Frame Depth	4 1/8"	4 1/8"	4 1/8"
Insulated Glass Thickness	7/8"	7/8"	7/8"
Air Infiltration (25 mph) (cfm/sqft)	0.15	0.15	0.01
Water Test Pressure (psf)	9.0	9.0	12.0
Structural Load (psf)	67.5	90	105
Operating Force (lbf)	45	45	n/a

Thermal Ratings	DH		Fixed
	Typical	Available	Typical
U Value Range	.63-.45	.43 - .38	.54 - .34
SHGC Range	.59-.30	.29 - .18	.71 - .35

Other certified thermal packages are available. Please contact WinTech for the most current ratings

NCTL-110-15421-01

The Wintech Series 9000 consists of 4 1/8" frame heavy commercial aluminum windows with poured urethane thermal barriers. Model 9000 is a double hung window with ratings of HC45:HC60 and Model 9500 is a fixed window with a rating of F-HC70. Both windows have the versatility of mulling and stacking. Twin or triple double hung windows may be supplied pre-assembled with common jamb mullions and continuous headers and sills. Windows are available with equal leg, 1 1/2" frame flanges for replacement or 1" for new construction applications, and are supplemented with a complete line of panning, trim, mullions, and other accessories.



15 Old Stonebreak Rd Malta NY 12020  
518-899-9000 • 518-899-4104fx

