

PRODUCT SUMMARY & PERFORMANCE DATA

11300AW Series uPVC/PVC Windows

AAMA 101/I.S. 2/A440-08	Casement	Awning	Hopper	Tilt & Turn	Fixed Lite Interior Glaze
AAMA Rating	C-AW90	C-AW100	P-AW100	P-AW65	F-AW100
Test Size	36 x 60	60 x 36	60 x 36	60 x 99	60 x 99
Frame Depth	3 1/4"	3 1/4"	3 1/4"	3 1/4"	3 1/4"
Insulated Glass Thickness	1" - 1 9/16"	1" - 1 9/16"	1" - 1 9/16"	1" - 1 9/16"	1" - 1 9/16"
Air Infiltration @ 6.24 (50 mph) (cfm/sqft)	0.07	0.09	0.03	0.05	0.01
Water Test Pressure (psf)	15.0	15.0	12.0	15.0	15.0
Structural Load (psf)	135	150	150	97.7	150
U-Value range	.18 - .34	.18 - .35	.18 - .35	.16 - .38	.14 - .45
SHGC range	.10 - .28	.10 - .28	.10 - .28	.18 - .51	0.22 - 0.61
Condensation Resistance range	51-77	51-77	51-77	46-74	46-74
STC Range	33-43	33-43	33-43	33-43	32-46
OITC Range	26-37	26-37	26-37	26-37	26-38

The Wintech Series 11300 consists of 3 1/4" frame heavy commercial uPVC windows with both structural integrity and energy efficiency. Series 11300 consists of Outswing and Inswing casements, Awning, Hopper and Fixed Lite windows. All windows have the versatility of mulling and stacking. Windows may be supplied pre-assembled or provided with components to mull in field. These windows are available with equal leg frames and new construction fin frames for replacement or new construction applications.

The windows are supplemented with a complete line of receptors, trim, and other accessories and are available with a range of base colors in addition to exterior SuperCap or int/ext SuperCap coordinating with popular architectural finishes.



15 Old Stonebreak Rd Malta NY 12020
 518-899-9000 • 518-899-4104fx

www.windowtechsystems.net

